

**120H1810****Scroll compressor, DSH184A3ALD**

Refrigerants: R452B; R410A; R454B, Segment usage: Air conditioning, Compressor power supply [V]: 208-230/3/60, Packing format: Single pack

**PRODUCT DETAILS**

<b>Gross weight</b>	76.12 Kilogram
<b>Net weight</b>	73.62 Kilogram
<b>Volume</b>	190.665 Cubic decimeter
<b>EAN</b>	5702424601126
<b>Type</b>	DSH184
<b>Product group</b>	Hermetic compressors
<b>Product Name Description</b>	Scroll compressor DSH
<b>Brand technique</b>	Scroll compressor
<b>Capacity control</b>	Fixed speed
<b>CE evaluated</b>	Yes
<b>China RoHS compliance</b>	Yes with exemptions
<b>Colour</b>	Blue
<b>Compressor power supply [V]</b>	208-230/3/60
<b>Configuration code</b>	Single
<b>Connection type</b>	Brazed
<b>Contain batteries</b>	No
<b>Description</b>	DSH184-3
<b>Diameter [mm]</b>	243 mm
<b>Discharge connection height [mm]</b>	525 mm
<b>Discharge connection pipe size [in]</b>	7/8 in
<b>Discharge connection size [in]</b>	7/8 in
<b>Drawing number</b>	8560235
<b>Economizer</b>	No
<b>EU RoHS compliance</b>	Yes with exemptions
<b>EU RoHS exemption clause</b>	7(c)-I 6(a) 6(a)-I 6(c) 7(a) 8(b)
<b>Family</b>	DSH
<b>Fitting standard</b>	ODF
<b>Frequency [Hz]</b>	60
<b>Gauge port HP</b>	None
<b>Gauge port LP</b>	Schrader
<b>Glass mounting</b>	Threaded
<b>Glass torque [Nm]</b>	50 N-m
<b>High Side TS Max</b>	150 °C
<b>High Side TS Min</b>	-35 °C

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Product Detail | Scroll compressor, DSH184A3ALD

## PRODUCT DETAILS

High Side Volume	0.7 L
High value of nominal voltage at 60Hz [V]	230 V
High value of voltage range at 60Hz [V]	253 V
IDV	Yes
In scope of WEEE	No
IP protection class	IP54 (with cable gland)
Low Side TS Max	55 °C
Low Side TS Min	-35 °C
Low Side Volume	13.9 L
Low value of nominal voltage at 60Hz [V]	208 V
Low value of voltage range at 60Hz [V]	187 V
LRA	351 A
Max pressure (PS) - high side	48.7 bar
Max pressure (PS) - low side	33.3 bar
Maximum Operating Current [MOC]	71 A
Model number	DSH184A3ALD
Motor protection	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	208-230/3/60
Number of starts per hour [Max]	12
Oil charge [L]	3.6 L
Oil equalization	1-3/4" Rotolock
Oil reference	160SZ
Oil type	POE
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Screw 4.8 mm
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerant charge [kg] [Max]	10 kg
Refrigerants	R410A R452B R454B
RLA	53.6 A
Rotational speed at 60Hz [rpm]	3500 rpm
SCIP dossier no.	bff3e2c3-5aad-40f0- b874-7eee67aaf788
SCIP dossier product name	CSHD092-183/DSF090-200/ DSH090-184/SH090-184/SJ161/ WSH090-184
Segment usage	Air conditioning
Suction connection height [mm]	300 mm
Suction connection material	-
Suction connection pipe size [in]	1 3/8 in
Suction connection size [in]	1 3/8 in
Swept volume [cm <sup>3</sup> ]	170.3 cm <sup>3</sup>
Technology	Scroll
Test dif [bar] [Max]	37 bar

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**Product Detail | Scroll compressor, DSH184A3ALD**

---

**PRODUCT DETAILS**

<b>Test HP [bar] [Max]</b>	48.7 bar
<b>Test LP [bar] [Max]</b>	33.3 bar
<b>Torque earth [Nm]</b>	2 N-m
<b>Torque power [Nm]</b>	3 N-m
<b>Total height [mm]</b>	555 mm
<b>UL evaluated</b>	Yes
<b>Viscosity [cP]</b>	32 cP
<b>Winding resistance for three-phase compressors with identical windings [Ohm]</b>	0.22 Ohm

---