

# L Series Recovery Unit



Built in pressure gauge

One key operation

Self-purge function

Oil free compressor

Cooling fan



## Light • Fast

### One Key Operation

- Easy to use

### Self-purge Function

- Prevent mixing of various refrigerants

### Oil-free Compressor

- Suitable for all commonly used refrigerants

### High Pressure Protection

- Safe to use

Model	VRR12L			VRR12L-OS		
Refrigerant	Categories III : R12, R134a, R401C, R500 Categories IV : R22, R401A, R401B, R402B, R407C, R407D, R408A, R409A, R411A, R411B, R412A, R502, R509 Categories V : R402A, R404A, R407A, R407B, R410A, R507					
Power Supply	220-240V~/50-60Hz	115V~/60Hz	220V-240V~/50-60Hz	115V~/60Hz		
Motor	3/4 HP	3/4 HP	3/4 HP	3/4 HP		
Motor Speed	1450 rpm/1750 rpm	1750 rpm	1450 rpm/1750 rpm	1750 rpm		
Maximal Current Draw	4 A	8 A	4 A	8 A		
Compressor	Oil-less, Air-cooled, Piston style					
Automatic Safety Shut-Off	38.5bar/3850kPa(558psi)					
Recovery Rate (kg/min)	Categories III	Categories IV	Categories V	Categories III	Categories IV	Categories V
	Vapor	0.20	0.25	0.25	0.20	0.25
	Liquid	1.60	1.80	2.20	1.60	1.80
	Push/Pull	4.60	5.60	6.30	4.60	5.60
Operating Temperature	0°C-40°C					
Dimensions	400×250×355 mm					
Weight	13.0 kg			14.2 kg		